



Safety Data Sheet

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: CERASEAL

Recommended Use: Ceramic protector.

Supplier: Selleys - A Division of ORICA NEW ZEALAND LIMITED

Street Address: The Gate Industrial Park, 373 Neilson St
Onehunga, Auckland
New Zealand

Telephone Number: +64 9 820 4852

Facsimile: 0 800 804 583

Emergency Telephone: 0 800 734 607 (ALL HOURS)

2. HAZARDS IDENTIFICATION

Not classified as a Dangerous Good under NZS 5433:2007 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

Subclasses: Subclass 6.3 Category B - Substances that are mildly irritating to the skin.
Subclass 6.4 Category A - Substances that are irritating to the eye.

Cleaning Products (Subsidiary Hazard) Group Standard 2006

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components / CAS Number	Proportion	Risk Phrases
Silicone	10-<30%	-
-		
Ethyl alcohol	10-<20%	R11
64-17-5		
Propylene glycol	1-<10%	-
57-55-6		
Ingredients determined not to be hazardous	to 100%	-
-		

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (Phone eg. Australia 131 126; New Zealand 0 800 764766) or a doctor.

Inhalation: Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

Product Name: CERASEAL
Substance No: 00000022041

Issued: 07/11/2008

Version: 1



Safety Data Sheet

Skin Contact: If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

Eye Contact: If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.

Ingestion: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

Medical attention and special treatment: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazards from combustion products: Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning will emit toxic fumes, including those of oxides of carbon .

Precautions for fire fighters and special protective equipment: Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media: Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures: If contamination of sewers or waterways has occurred advise local emergency services.

Methods and materials for containment and clean up: SMALL SPILLS: Slippery when wet. Avoid accidents, clean up immediately. Wipe up with rag or absorbent paper.
LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Keep out of reach of children. Avoid eye contact and repeated or prolonged skin contact.

Product Name: CERASEAL
Substance No: 00000022041

Issued: 07/11/2008

Version: 1



Safety Data Sheet

Conditions for safe storage: Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from foodstuffs. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

No value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH). However, Workplace Exposure Standard(s) for constituent(s):

Ethyl alcohol: 8hr WES-TWA = 1,000 ppm (1,880 mg/m³)

Propane-1,2-diol (propylene glycol) (vapour & particulates): WES-TWA 150 ppm, 474 mg/m³; (particulates only): WES-TWA 10 mg/m³.

As published by the New Zealand Occupational Safety and Health Service (OSH).

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering controls:

Natural ventilation should be adequate under normal use conditions. Keep containers closed when not in use.

Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Blue



MANUFACTURE, PACKAGING AND TRANSPORT: Blue - Wear clean overalls, safety boots, general purpose gloves (PVC) and full face visor. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

FOR CONSUMER USE: Avoid contact with eyes and skin. Wear rubber gloves and eye protection while handling the product. Wash hands after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Product Name: CERASEAL
Substance No: 00000022041

Issued: 07/11/2008

Version: 1



Safety Data Sheet

Physical state:	Gel
Colour:	Opaque
Odour:	Mild Solvent
Solubility:	Soluble in water.
Specific Gravity:	0.99 @20 °C
Relative Vapour Density (air=1):	N Av
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	N App
Flammability Limits (%):	N App
Autoignition Temperature (°C):	N App
% Volatile by Weight:	N Av
Boiling Point/Range (°C):	N Av
Sublimation Point (°C):	N App
pH:	7-8
Viscosity:	N Av
Evaporation Rate:	N Av

10. STABILITY AND REACTIVITY

Chemical stability:	Stable under normal conditions of use.
Conditions to avoid:	Avoid contact with foodstuffs.
Incompatible materials:	Incompatible with oxidising agents .
Hazardous decomposition products:	Oxides of carbon. Oxides of sulfur.
Hazardous reactions:	None known.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting, diarrhoea, and abdominal pain.
Eye contact:	An eye irritant.
Skin contact:	Repeated or prolonged skin contact may lead to irritation.

Product Name: CERASEAL
Substance No: 000000022041

Issued: 07/11/2008 **Version:** 1
Page 4 of 6



Safety Data Sheet

Inhalation: Where this material is used in a poorly ventilated area, at elevated temperatures or in confined spaces, vapour may cause irritation to mucous membranes of the respiratory tract, headache and nausea.

Long Term Effects:
No information available for the product.

Toxicological Data:
No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal methods: Refer to Waste Management Authority. Dispose of material through a licensed waste contractor.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as a Dangerous Good under NZS 5433:2007 Transport of Dangerous Goods on Land.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification: Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

Subclasses: Subclass 6.3 Category B - Substances that are mildly irritating to the skin.
Subclass 6.4 Category A - Substances that are irritating to the eye.

Cleaning Products (Subsidiary Hazard) Group Standard 2006

16. OTHER INFORMATION

This material safety data sheet has been prepared by SH&E Shared Services, Orica.
For further copies of this sheet or other product information contact Selley's Proprietary Limited Customer Service.
Phone: 1300 555 205 (Australia wide)

Product Name: CERASEAL
Substance No: 00000022041

Issued: 07/11/2008 **Version:** 1



Safety Data Sheet

Fax: 1300 555 305 (Australia wide)
Phone: 9 820 4852 (New Zealand)
Fax: 0800 804 583 (New Zealand)

Reason(s) for Issue:

First Issue Primary MSDS

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Orica Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Orica representative or Orica Limited at the contact details on page 1.

Orica Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: CERASEAL
Substance No: 000000022041

Issued: 07/11/2008

Version: 1