



Material Safety Data Sheet

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: STEEL POWER

Recommended Use: Cleaner & polish for stainless steel.

Supplier: Selleys Pty Ltd

ABN: 67 000 049 427

Street Address: 1 Gow Street

Padstow 2211

Australia

Telephone Number: +61 2 9781 8777

Facsimile: +61 2 9781 8825

Emergency Telephone: 1 800 033 111 (ALL HOURS)

2. HAZARDS IDENTIFICATION

Based on available information, not classified as hazardous according to criteria of ASCC; NON-HAZARDOUS SUBSTANCE.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Poisons None allocated.

Schedule:

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Components / CAS Number | Proportion | Risk Phrases |
|--|------------|--------------------------|
| Crystalline silica (Quartz) 14808-60-7 | 10-<30% | R48/20, Carc. Cat. 1 R49 |
| Citric acid 77-92-9 | 1-<10% | R41 |
| Ingredients determined not to be hazardous | to 100% | - |
| - | | |

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (Phone eg. Australia 131 126; New Zealand 0 800 764766) or a doctor.

Product Name: STEEL POWER
Substance No: 00000022049

Issued: 05/11/2008

Version: 1



Material Safety Data Sheet

- Inhalation:** Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.
- Skin Contact:** If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.
- Eye Contact:** If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.
- Ingestion:** If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.
- Medical attention and special treatment:** Treat symptomatically.

5. FIRE FIGHTING MEASURES

- Hazards from combustion products:** Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning will emit toxic fumes, including those of oxides of carbon .
- Precautions for fire fighters and special protective equipment:** Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.
- Suitable Extinguishing Media:** Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

- Emergency procedures:** If contamination of sewers or waterways has occurred advise local emergency services.
- Methods and materials for containment and clean up:** SMALL SPILLS: Slippery when wet. Avoid accidents, clean up immediately. Wipe up with rag or absorbent paper.
LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

- Conditions for safe storage:** Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from

Product Name: STEEL POWER
Substance No: 00000022049

Issued: 05/11/2008 **Version:** 1



Material Safety Data Sheet

foodstuffs. Keep containers closed when not in use - check regularly for leaks.

Precautions for safe handling: Keep out of reach of children. Avoid eye contact and repeated or prolonged skin contact.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

Silica Crystalline - Quartz: 8hr TWA = 0.1 mg/m³

As published by the National Occupational Health and Safety Commission.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering controls:

Natural ventilation should be adequate under normal use conditions. Keep containers closed when not in use.

Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Green



MANUFACTURE, PACKAGING AND TRANSPORT: Green - Wear clean overalls, safety boots, general purpose gloves (PVC) and safety spectacles. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

FOR CONSUMER USE: No special personal protective equipment required. Wash hands after use. Rubber gloves are recommended if handling often.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Viscous liquid

Product Name: STEEL POWER
Substance No: 00000022049

Issued: 05/11/2008

Version: 1



Material Safety Data Sheet

Colour: Green Opaque
Odour: Lemon

Solubility: Dispersible in water.
Specific Gravity: 1.13 @20 °C
Relative Vapour Density (air=1): N Av
Vapour Pressure (20 °C): 3.2 kPa @ 20° C
Flash Point (°C): N App
Flammability Limits (%): N App
Autoignition Temperature (°C): N App
% Volatile by Weight: N Av
Melting Point/Range (°C): N Av
Boiling Point/Range (°C): 100° C (water)
Decomposition Point (°C): N Av
Sublimation Point (°C): N App
pH: 2
Viscosity: N Av
Evaporation Rate: N Av

10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions of use.

Conditions to avoid: Avoid contact with foodstuffs.

Incompatible materials: Incompatible with alkalis and oxidising agents .

Hazardous decomposition products: Oxides of carbon.

Hazardous reactions: None known.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: No adverse effects expected, however, large amounts may cause nausea and vomiting.

Eye contact: May be an eye irritant.

Skin contact: Repeated or prolonged skin contact may lead to irritation.

Product Name: STEEL POWER
Substance No: 000000022049

Issued: 05/11/2008

Version: 1



Material Safety Data Sheet

Inhalation: Breathing in mists or aerosols may produce respiratory irritation.

Long Term Effects:

No information available for the product.

Toxicological Data:

No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal methods: Refer to Waste Management Authority. Normally suitable for disposal at approved land waste site.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification: Based on available information, not classified as hazardous according to criteria of ASCC; NON-HAZARDOUS SUBSTANCE.

Poisons Schedule: None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Product Name: STEEL POWER
Substance No: 00000022049

Issued: 05/11/2008

Version: 1



Material Safety Data Sheet

This material safety data sheet has been prepared by SH&E Shared Services, Orica.

For further copies of this sheet or other product information contact Selley's Proprietary Limited Customer Service.

Phone: 1300 555 205 (Australia wide)

Fax: 1300 555 305 (Australia wide)

Phone: 9 820 4852 (New Zealand)

Fax: 0800 804 583 (New Zealand)

Reason(s) for Issue:

First Issue Primary MSDS

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Orica Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Orica representative or Orica Limited at the contact details on page 1.

Orica Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: STEEL POWER
Substance No: 000000022049

Issued: 05/11/2008

Version: 1